



# GREEN2



### Main features:

Power up to 2.5 kW, from 24V up to 96V,  
from 17A up to 70A

Programmable via USB type A/B port or via display  
Graphical display

**DIMENSIONS (LxWxH):** 300x475x180 mm  
11.81x18.70x7.09 in.

**WEIGHT:** 11 Kg – 24.25 lbs

**PROTECTION GRADE** IP20

**INPUT VOLTAGE:** 120/200-240 Vac

Battery Voltage	IUIa Wet 8h Range (C5)	IUIa Wet 12h Range (C5)	IUIa Gel PzV 10-14h Range (C5)	Charging Current	Model
24V	280 ÷ 340 Ah	450 ÷ 550 Ah	350 ÷ 420 Ah	50A	24-50
	340 ÷ 410 Ah	540 ÷ 660 Ah	420 ÷ 510 Ah	60A	24-60
	390 ÷ 480 Ah	630 ÷ 770 Ah	480 ÷ 590 Ah	70A	24-70
36V	230 ÷ 280 Ah	360 ÷ 440 Ah	275 ÷ 340 Ah	40A	36-40
	250 ÷ 310 Ah	410 ÷ 500 Ah	310 ÷ 380 Ah	45A	36-45
48V	170 ÷ 210 Ah	270 ÷ 330 Ah	210 ÷ 255 Ah	30A	48-30
	230 ÷ 280 Ah	360 ÷ 440 Ah	275 ÷ 340 Ah	40A	48-40
72V	140 ÷ 170 Ah	230 ÷ 280 Ah	175 ÷ 210 Ah	25A	72-25
80V	110 ÷ 140 Ah	180 ÷ 220 Ah	140 ÷ 170 Ah	20A	80-20
96V	100 ÷ 120 Ah	155 ÷ 190 Ah	115 ÷ 145 Ah	17A	96-17

